


LEGEND

KEATING COEFFICIENTS

Positive correlation		Negative correlation
	90%	
	85%	
	80%	
	75%	

MAGNETIC CONTOURS


- 10 nT contour
- 50 nT contour
- 200 nT contour
- 1000 nT contour
- Magnetic depression

OTHER SYMBOLS

(Some symbols may not apply to this map)

- Drainage
- Main road
- Secondary road
- Trail
- Power line
- Pipeline
- Administrative boundary
- Railroad

RESIDUAL MAGNETIC FIELD GRID



DESCRIPTIVE NOTES

Introduction

This survey was flown using an aircraft equipped with the Fugro Triaxial Gradiometer system. The aircraft was also equipped with a GPS navigation system and a digital data acquisition system.

Residual Magnetic Field Map

The contours of residual magnetic intensity were generated from digitally recorded data. The magnetic data was corrected for diurnal variations, levelled to the control lines and interpolated onto a 30 m regular grid, using the gradient-enhanced bi-directional algorithm. An International Geomagnetic Reference Field (IGRF) correction was applied to the total magnetic field data at survey altitude using the 2000 model year extrapolated to 2003.5 (December 1, 2003). A regional correction was applied to level the magnetic field to the Ontario Master Aeromagnetic Grid.

Keating Correlation Coefficients

Possible kimberlite targets have been identified from the residual magnetic intensity data, based on the identification of roughly circular anomalies. This procedure was automated by using a known pattern-recognition technique (Keating 1995), which consists of computing, over a moving window, a first-order regression between a vertical cylinder model anomaly and the gridded magnetic data. Only the results where the absolute value of the correlation coefficient is above a threshold of 75% were retained. The results are depicted as circular symbols, scaled to reflect the correlation value. The most favourable targets are those that exhibit a cluster of high amplitude solutions. Correlation coefficients with a negative value correspond to reversely magnetized sources. It is important to be aware that other magnetic sources may correlate well with the vertical cylinder model, whereas some kimberlite pipes of irregular geometry may not.
The cylinder model parameters are as follows:
Cylinder diameter: 200 m
Cylinder length: infinite
Overburden thickness: 8 m
Magnetic inclination: 73.99 °N
Magnetic declination: 11.54 °W
Window size: 18 x 18 cells (540 m x 540 m)

SURVEY PARAMETERS

AIRCRAFT
Type: Grand Caravan 208B
Registration: C-GNCA

MAGNETOMETER
Type: Scintrex CS-2
Sensitivity: 0.001 nT
Noise level: < 0.10 nT
Sample interval: 10 readings per second
Sensor locations:
tail stinger top
tail stinger bottom
left wingtip
right wingtip

MAGNETIC COMPENSATION SYSTEM
Type: RMS AADCII
Range: 20 000 to 100 000 nT
Resolution: 1 picotesla
Accuracy of compensation: 0.035 nT

NAVIGATION SYSTEM
Navigation console: Picodas PNAV 2100
GPS receiver: Novatel
Differential GPS receiver: Omnistar
GPS sampling interval: 1 reading per second
Radar altimeter: Collins 58B
Radar sample interval: 1 reading per second
Barometric altimeter: Rosemount PN 1241
Barometric sample interval: 1 reading per second
Video flight path recorder: Panasonic AG-2400

DATA ACQUISITION SYSTEM
Digital acquisition system: GeoDAS
Analog chart recorder: RMS GR33

BASE STATION
Magnetometer: Scintrex CS-2
Magnetometer sample interval: 1 reading per second
Backup magnetometer: GSM 19
Magnetometer sample interval: 1 reading per 3 seconds
GPS receiver: Trimble
GPS sample interval: 1 reading per second

SURVEY SPECIFICATIONS
Survey date: October 19, 2003 to January 20, 2004
Nominal aircraft terrain clearance: 80 m
Traverse line spacing: 150 m
Control line spacing: 5000 m
Traverse line direction: N-S
Control line direction: E-W

COORDINATE SYSTEM
Projection: Universal Transverse Mercator
Datum: NAD83
Central meridian: 81°00'W (UTM zone 17N)
Central scale factor: 0.9996
False easting: 500 000 m
False northing: 0 m

Ontario

Ontario Geological Survey

MAP 81 878

AIRBORNE MAGNETIC SURVEY

Colour-filled contours of the residual magnetic field and Keating coefficients

ROUND LAKE BATHOLITH AREA


Scale 1:50 000

1 km 0 2 km

NTS References: 41 P/9,10,15,16

© Queen's Printer for Ontario, 2004.

This map is published with the permission of the Director, Ontario Geological Survey.



Location map 1cm equals 30km

SOURCES OF INFORMATION

Base map information data derived from Ontario Land Information Warehouse, Land Information Ontario.

Magnetic declination in 2003 for the centre of the map area was 11.2169°W. Magnetic inclination in 2003 for the centre of the map area was 73968°N. Magnetic field strength was 57 149 nT. (Calculated using IGRF)

Keating, P.B. 1995. A simple technique to identify magnetic anomalies due to kimberlite pipes; Exploration and Mining Geology, v.4, no. 2, p.121-125.

CREDITS

Overall project management by Timmins Economic Development Corporation.

Contract management, project management by Robert Calhoun, Project Manager, Discover Abitibi Initiative.

Data acquisition, compilation and map production by Fugro Airborne Surveys.

Base maps and map surrounds by the Ontario Ministry of Northern Development and Mines, Sudbury, Ontario.

Quality assurance and quality control by Paterson, Grant & Watson Limited, Toronto, Ontario.

To enable the rapid dissemination of information, this map has not received a technical edit. Every possible effort has been made to ensure the accuracy of the information presented; however, the Ontario Ministry of Northern Development and Mines does not assume liability for any errors that may occur. Users can verify critical information from the corresponding digital profile and gridded data distributed by the Ontario Geological Survey.

Timmins

Discover Abitibi
A project of innovation, cooperation and revitalization

Découvrons l'Abitibi
Un projet d' innovation, de coopération et de renouvellement

Discover Abitibi Initiative

The Discover Abitibi Initiative is a regional, cluster economic development project based on geoscientific investigations of the western Abitibi greenstone belt. The initiative, centred on the Kirkland Lake and Timmins mining camps, will complete 19 projects developed and directed by the local stakeholders FedNor, Northern Ontario Heritage Fund Corporation and private sector investors have provided the funding for the initiative.

Initiative Découvrons l'Abitibi

L'initiative Découvrons l'Abitibi est un projet de développement économique régional dans une grappe d'industries, projet fondé sur des études géoscientifiques de la ceinture de roches vertes de l'Abitibi occidental. Cette initiative, centrée sur les zones minières de Kirkland Lake et de Timmins, mènera à bien 19 projets élaborés et dirigés par des intervenants locaux. FedNor, la Société de gestion du Fonds du patrimoine du Nord de l'Ontario et des investisseurs du secteur privé ont fourni les fonds de cette initiative.

Ontario Northern Ontario Heritage Fund
Fonds du patrimoine du Nord de l'Ontario

FedNor Canada

Issued 2004.

Information from this publication may be quoted if credit is given. It is recommended that reference be made in the following form:

Ontario Geological Survey 2004. Airborne magnetic survey, colour-filled contours of the residual magnetic field and Keating coefficients, Round Lake Batholith area; Ontario Geological Survey, Map 81 878, scale 1:50 000.